

Harness the Power of the Sun

SPTT-4200 PORTABLE TOWER TRAILER



Specifications

Portable, solar-powered 42 foot platform

Four (4) flooded lead-acid batteries 520 amp-hour capacity

320 Watt solar array

Nominal 75 amps per hour per day at 12.5 volt DC

(continuous operation)

Built-in 45 amp battery charger

Length Overall: 177 inches (449 cm)

Width Traveling: 91 inches (231 cm)

Width Operating: 139 inches (353 cm)

Height Traveling: 101 inches (256 cm)

Height Operating: 42 feet (1201 cm)

Ground Clearance: 13 inches (33 cm) min.

Weight: 2,800 lbs. (1,270 kg) approx. (max)

Tower Rating: Max Load: 45 lbs. (21 kg)

Max Surface Area: 5 sq ft (465 sq cm)



FEATURES

- Powerful tool for image data collection: 42 foot tower height maximizes viewing angles.
- Truly solar-powered: Continuous, year-round, uninterrupted power source capable of providing a minimum of 950 watt-hours per day of electrical power (nominal 75 amps per hour per day at 12.5 volts DC)
- Engineered mounting base: Designed to accommodate any size camera or related equipment
- Portable: Tower system can be towed to any location for temporary data collection
- Heavy-Duty: All steel trailer frame construction
- All aluminum telescoping tower with 1/8" aircraft cable guy wires -- exceptional rigidity and stability for user-supplied equipment
- Sturdy polyethylene fenders and lockable battery compartment
- Torsion-type suspension for a smooth ride and higher ground clearance
- Four (4) 3,000 lb. swivel jacks and tongue for easy leveling and setup
- Trailer-mounted solar array for optimum performance and efficiency
- Recessed taillights and retro-reflective decals





SPTT-4200 PORTABLE TOWER SYSTEM

SUGGESTED APPLICATIONS

The highly versatile Tower Trailer is adaptable to a wide variety of uses and equipment, such as:

- Security equipment
- Communications relay station
- Communications station
- Satellite dish
- Weather measurement sensors
- Wi-Fi hotspot

- Remote camera
- Acoustic data collection
- Police traffic control
- Homeland security
- Military zones
- Traffic studies
- Phased-array radar

AVAILABLE OPTIONS

- Auxiliary Battery Charger Upgrades -- 90 amp 120 volt AC, 55 amp 230 volt AC, 40 amp - 230 volts AC
- Battery Upgrade -- Flooded, Gel Cell or AGM maintenance-free batteries may be added up to a total of 16 batteries
- Solar Array Upgrade -- 480 watts
- Camera Systems -- Information about camera systems including Bosch, Pelco and Sur-Tec is available upon request

OTHER SOLAR TECH PRODUCTS

SILENT SENTINEL

Trailer and Truck Mount Arrow Boards

SILENT MESSENGER

Full-Size Trailer-Mount Message Boards

SILENT MESSENGER II

Mid-Size Trailer and Vehicle Mount Message Boards

SILENT MESSENGER III

Small-Size Trailer and Vehicle Mount Message Boards

SILENT MESSENGER IV

Small-Size Trailer and Vehicle Mount Message Boards

SILENT ADVISOR


Low and High-Speed Application Radar Speed Trailers

INCIDENT RESPONSE TRAILER

Work Zone Trailer with Cones and Barrels

SOLARTRAK

Monitoring and GPS Tracking of Construction Equipment





SOLAR TECHNOLOGY, INC.

7620 Cetronia Rd. Allentown, PA 18106 Phone: 800-475-5442 or 610-391-8600

www.solartechnology.com