



Silent Messenger III Message Board Mid-Sized

USES AND ADVANTAGES

The "Silent Messenger III" mid-sized message board is a truly reliable workhorse. A 27 x 48 pixel full matrix LED display on a sturdy steel trailer is powered by both solar panels and batteries.

Display sign panel measures 80" wide by 48" high, giving a clean crisp readable message. Available in either a foldable or a Lift and Rotate trailer.

OPTIONAL REMOTE COMMUNICATIONS AND GPS TRACKING!


When choosing this option, your Message Board will come with a GPS receiver, cellular transceiver, and **FREE lifetime cellular service***. Use with SolarTech's Command Center software for remote communication. This software allows you to track your equipment using the built-in cellular transceiver and GPS system.

Manage your fleet from your laptop, PC or smartphone... without leaving your desk! Access units from a map or list. Control units individually or broadcast to a group.

You can build a message library, share messages between boards, schedule messages and more.

Get automatic email notifications when a message changes, if the battery voltage is low, if a pixel or module fails, or the unit moves.


Keep tabs on your whole fleet. No more misplaced equipment... fewer problems... less downtime!



EASY-TO-USE CONTROLLER

The touch-screen controller needs no manual - it's that easy to use! Includes:

- Password protection
- Intuitive icons for ease of use
- Scheduling capability
- Fully networkable
- NTCIP version 3 compatible



Lift and Rotate
Model MB3-LR



Foldable
Trailer Mounted
Model MB3

Silent Messenger III Message Board

DISPLAY PANELS

Panel Size	80" x 47.5" (203.2 cm x 120.7 cm)
Pixel Size	1.50" x 1.50" (38 mm)
Character Height	7" to 30" (27 cm to 76 cm)
Matrix Size	27 x 48 pixels
Panel Construction	All aluminum, modular
Panel Face	3/16" polycarbonate, non-glare
Number of Fonts	Twelve (12)
Graphics Capability	Full matrix with full animation
Display Technology	LED (amber, 592 nm)
Display Brightness	>10,000 cd/m2 (candela per sq. meter)
Viewing Angle	>60°

TRAILER

	Standard Trailer	Lift & Rotate Trailer
Length Overall (operating)	112" (284 cm)	108" (274 cm)
Length Overall (traveling)	112" (284 cm)	152" (386 cm)
Width Overall	91" (231 cm)	77" (196 cm)
Width Across Fenders	75" (190 cm)	77" (196 cm)
Ground Clearance	13" (33 cm)	13" (33 cm)
Height Traveling	92" (234 cm)	101" (257 cm)
Height Operating	142" (360 cm)	142" (360 cm)
Weight	1,182 lbs (536 kg)	2,000 lbs. (907 kg) approx.
Coupler	2" (50 mm) ball or 2.5" (64 mm) pintle ring	2" (50 mm) ball or 3" (76 mm) pintle ring
Lifting Mechanism	1,000 lb. automatic brake, winch and cable	1,000 lb. electric linear actuator
Axle/Suspension	Torq flex, independent	Torq flex, independent

MEGA-TECH CONTROL CONSOLE

Console Circuitry	Ultra-low power solid state
Console Touchscreen	Weather-resistant, backlit, full-color GUI, intuitive icon-driven, multi-lingual: five international languages
Programming Software	Proprietary, field upgradable (for units that are not connected to Command Center)
Message Capacity	Pre-programmed and user-programmed: > 250 each
Time-Date Control	Real-time clock/calendar (365 day)
Message Display Time	User-selectable (0.1 to 99 seconds)
Display Update Time	Instantaneous
Non-Volatile Memory	16 GB Micro SD card
Password Protection	User-selectable, multi-level
Operator Interface	Easy-to-use icons (no manual required)
Connectivity	Networkable (wired or wireless) and NTCIP compatible (Ethernet & RS-232)

ENERGY SOURCE

Operating Voltage	12 volts DC (nominal)
Battery Type	6 volt heavy duty, deep cycle (GC-2)
Number of Batteries	Four (4) standard lead acid (flooded)
Battery Bank Capacity	520 amp hours
Battery Status Indicator	Displays battery voltage, charging activity and low battery condition
Solar Construction	Top-mounted solar panels in aluminum frame
Solar Power Output	Standard 160 watt (nominal)
Solar Charge Controller	Automatic, temperature compensated, MPPT (Maximum Power Point Tracking)



SCAN ME



SOLAR TECHNOLOGY, INC.
7620 Cetronia Rd. Allentown, PA 18106
Phone: 800-475-5442 or 610-391-8600

P/N 500-023-010 Rev. L 2022



MB III lowered and
folded compactly for
transport.

OPTIONS AND UPGRADES

UPGRADES - FOR LIFT AND ROTATE TRAILER ONLY

Tilt and Rotate Solar Arrays:
• 220 watt • 330 watt

SOLAR ARRAY UPGRADES - BOTH TRAILERS

Fixed Solar Arrays: • 220 watt • 270 watt • 330 watt

REMOTE COMMUNICATIONS

Includes GPS receiver, cellular transceiver, and FREE cellular service.* Remotely access and track your Message Board.
*With this option, cellular service is provided free of charge, and is limited to carrier supported generational wireless technology.

BATTERY UPGRADES

Type	Number	Capacity
Lead-Acid (flooded)	Six (6) Eight (8)	780 amp hour 1040 amp hour
Gel Cell or AGM (maintenance-free)	Four (4) Six (6) Eight (8)	520 amp hour 780 amp hour 1040 amp hour

BATTERY CHARGER OPTIONS

• 45 amp, 120 volt AC • 55 amp, 120 volt AC • 90 amp, 120 volt AC

BRAKE OPTIONS


Hydraulic surge brakes (5,000 lb. capacity) or Electric brakes

SECURITY OPTION

- Anti-theft steel security frame bolted to trailer
- Vandal-Proof Battery Box reinforced steel cage

RADAR OPTIONS

Directional doppler K-Band, user-configured KPH or MPH. Data collection and statistical analysis package is included.



Custom Colors
available



Made in the USA

www.solartechology.com